

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 1 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

SECTION 1: Identification

Product identifier

Product name: WarFighter Fuel Treatments Corrosion Spray

Product code: WFFT-CS-0001



Recommended use of the product and restriction on use

Relevant identified uses: Cleaner

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

WarFighter Fuel Treatments, LLC
1809 East Broadway Street
Suite 326
Oviedo, Florida, 32765
1-407-923-6221

Emergency telephone number:

United States

WarFighter Fuel Treatments, LLC
1-407-923-6221

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 2

Skin corrosion, category 1B

Serious eye damage, category 1

Acute toxicity (oral), category 4

Acute toxicity (inhalation), category 4

Specific target organ toxicity - single exposure, category 1

Carcinogenicity, category 2

Reproductive toxicity, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapor.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H302 Harmful if swallowed.

H332 Harmful if inhaled.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 2 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

- H370 Causes damage to organs.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.

Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash skin and eyes thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P281 Use personal protective equipment as required.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P370+P378 In case of fire: Use agents recommended in Section 5 for extinction.
- P310 Immediately call a POISON CENTER or doctor/physician.
- P321 Specific treatment (see supplemental first aid instructions on this label).
- P363 Wash contaminated clothing before reuse
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P330 Rinse mouth
- P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P307+P311 If exposed: Call a POISON CENTER or doctor/physician.
- P308+P313 If exposed or concerned: Get medical advice/attention
- P403+P235 Store in a well ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: None

Supplemental label elements:

- 4 percent of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 2 percent of the mixture consists of ingredient(s) of unknown acute inhalation toxicity

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 1330-20-7	Xylene	4.5-9
CAS number: 100-41-4	Ethyl Benzene	1.5-3

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 3 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

CAS number: 67-56-1	Methanol	3-5
CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	0.3-1.5
CAS number: 84852-15-3	Nonyl phenol	0.03-0.3
CAS number: N/A	Denaturant	1.3-1.75
CAS number: 64-17-5	Ethanol	67-69
CAS number: 64-19-7	Acetic Acid	<0.01

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position
Maintain an unobstructed airway
Get medical advice/attention if you feel unwell
Take precautions to ensure your own safety
Remove source of exposure or move person to fresh air and keep comfortable for breathing
Immediately call a POISON CONTROL CENTER or seek medical attention
If breathing has stopped, trained personnel should begin rescue breathing
Avoid mouth-to-mouth contact by using a barrier device
If the heart has stopped, immediately start cardiopulmonary resuscitation (CPR)

After skin contact:

Rinse affected area with soap and water
If symptoms develop or persist, seek medical attention
Avoid direct contact and wear chemical protective clothing, if necessary
Immediately take off all contaminated clothing
Gently blot or brush away excess product
Rinse skin with lukewarm, gently flowing water until medical aid is available
Immediately call a POISON CONTROL CENTER or seek medical attention
Wash contaminated clothing before re-use or discard

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes
If symptoms develop or persist, seek medical attention
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open
Remove contact lenses, if present and easy to do so
Continue rinsing until medical aid is available
Immediately call a POISON CONTROL CENTER or seek medical attention
Avoid direct contact and wear chemically protective eyewear, if necessary

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 4 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

After swallowing:

- Rinse mouth thoroughly
- Seek medical attention if irritation, discomfort, or vomiting persists
- Immediately call a POISON CONTROL CENTER or seek medical attention
- Do not induce vomiting and rinse mouth
- If vomiting occurs naturally, lie on your side, in the recovery position
- If breathing has stopped, trained personnel should begin rescue breathing
- Avoid mouth-to-mouth contact by using a barrier device
- If the heart has stopped, immediately start cardiopulmonary resuscitation (CPR)

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

- Headache, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue
- Reddening, itching and inflammation of the skin
- May cause severe eye irritation with pain, tearing, burning feeling, sensitivity to light, swelling and possible corneal damage

Delayed symptoms and effects:

- Defatting of the skin which can lead to drying, cracking and/or dermatitis
- Breathing high concentrations of this material can cause irregular heart beats which can cause death

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

- Thermal decomposition can lead to release of irritating gases and vapors
- Vapors can flow to distant ignition sources and flashback
- Liquid is volatile and may generate an explosive atmosphere
- May form corrosive mixtures with water

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

- Shut off sources of ignition
- Carbon monoxide and carbon dioxide may form upon combustion
- Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

- Ensure adequate ventilation
- Ensure air handling systems are operational

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 5 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

Wear protective eye wear, gloves and clothing
Beware of vapors accumulating to form explosive concentrations
Vapors can accumulate in low areas

Environmental precautions:

Should not be released into the environment
Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing
Use spark-proof tools and explosion-proof equipment
Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)
Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Use only with adequate ventilation.
Avoid breathing mist or vapor.
Do not eat, drink, smoke or use personal products when handling chemical substances.
Take precautionary measures against electrostatic discharges.
Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.
Protect from freezing and physical damage.
Store in a cool, well-ventilated area.
Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Ethanol	64-17-5	ACGIH TLV TWA 1,000 ppm
	Xylene	1330-20-7	ACGIH TLV TWA 100 ppm
	Acetic Acid	64-19-7	ACGIH TLV TWA 10 ppm
	Xylene	1330-20-7	ACGIH TLV STEL 150 ppm
	Acetic Acid	64-19-7	ACGIH TLV STEL 15 ppm
	Methanol	67-56-1	ACGIH TLV STEL 250 ppm [skin]
	Methanol	67-56-1	ACGIH TLV TWA 200 ppm [skin]
	Ethanol	64-17-5	ACGIH TLV STEL 1,000 ppm
	Ethyl Benzene	100-41-4	ACGIH TLV 20 ppm
United States (OSHA)	Methanol	67-56-1	OSHA PEL TWA 200 ppm
	Methanol	67-56-1	OSHA PEL TWA 260 mg/m ³
	Ethanol	64-17-5	OSHA PEL TWA 1,000 ppm
	Xylene	1330-20-7	OSHA PEL TWA 435 mg/m ³

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 6 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Ethanol	64-17-5	OSHA PEL TWA 1,900 mg/m ³
	Ethyl Benzene	100-41-4	OSHA PEL TWA 100 ppm
	Acetic Acid	64-19-7	OSHA PEL TWA 10 ppm
	Acetic Acid	64-19-7	OSHA PEL TWA 25 mg/m ³
	Ethyl Benzene	100-41-4	OSHA PEL TWA 435 mg/m ³
	Xylene	1330-20-7	OSHA PEL TWA 100 ppm
	Xylene	1330-20-7	OSHA STEL 150 ppm
	Xylene	1330-20-7	OSHA STEL 655 mg/m ³
	Solvent naphtha (petroleum), light arom.	64742-95-6	OSHA Z-1 PEL: 100 ppm / 400 mg/m ³ .
NIOSH	Ethanol	64-17-5	NIOSH REL TWA 1,000 ppm
	Acetic Acid	64-19-7	NIOSH REL TWA 10 ppm
	Methanol	67-56-1	NIOSH REL TWA 200 ppm [skin]
	Xylene	1330-20-7	NIOSH REL TWA 435 mg/m ³
	Ethyl Benzene	100-41-4	NIOSH REL TWA 100 ppm
	Methanol	67-56-1	NIOSH REL TWA 260 mg/m ³ [skin]
	Ethanol	64-17-5	NIOSH REL TWA 1,900 mg/m ³
	Acetic Acid	64-19-7	NIOSH REL TWA 25 mg/m ³
	Xylene	1330-20-7	NIOSH REL TWA 100 ppm
	Acetic Acid	64-19-7	NIOSH REL ST 15 ppm
	Ethyl Benzene	100-41-4	NIOSH REL TWA 435 mg/m ³
	Methanol	67-56-1	NIOSH REL ST 250 ppm [skin]
	Xylene	1330-20-7	NIOSH REL ST 150 ppm
	Ethyl Benzene	100-41-4	NIOSH REL ST 125 ppm
	Xylene	1330-20-7	NIOSH REL ST 655 mg/m ³
	Acetic Acid	64-19-7	NIOSH REL ST 37 mg/m ³
	Methanol	67-56-1	NIOSH REL ST 325 mg/m ³ [skin]
	Ethyl Benzene	100-41-4	NIOSH REL ST 545 mg/m ³
		Solvent naphtha (petroleum), light arom.	64742-95-6

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 7 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Light amber to clear liquid
Odor	Mild
Odor threshold	Not available
pH	Not available
Melting point/freezing point	Not available
Initial boiling point/range	> 150 °F (> 65.6 °C)
Flash point (closed cup)	< 32 °F (< 0 °C) Pensky-Martens Closed Cup (ASTM D93)
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	19%
Lower flammability/explosive limit	1.4%
Vapor pressure	7.91 kPa at 25 °C
Vapor density	1.59
Density	0.789 g/cm ³ estimated
Relative density	0.791 - 0.793 (68 °F (20 °C))
Solubilities	Very soluble
Partition coefficient (n-octanol/water)	-0.31 (as ethanol)
Auto/Self-ignition temperature	Not available
Decomposition temperature	Not available
Dynamic viscosity	0.5 mPa.s (158 °F (70 °C))
Kinematic viscosity	Not available
Explosive properties	Not available
Oxidizing properties	Not available

Other information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 8 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

Excess heat, ignition source or flames.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Harmful if swallowed Harmful if inhaled

Product data: No data available.

Substance data:

Name	Route	Result
Methanol	oral	LD50 - Rat - 5630 mg/kg
	dermal	LD50 - Rabbit - 15800 mg/kg
	inhalation	LC50 - Rat - 83.9 mg/l - 4h
Xylene	inhalation	LC50 - Rat - 5,000 ppm/4 h
	dermal	LD50 - Rabbit - > 1,700 mg/kg
	oral	LD50 - Rat - 4,300 mg/kg
Ethyl Benzene	inhalation	LCLo - Rat - 4,000ppm/4 h
Nonyl phenol	oral	LD50 - Rat - 1,300 mg/kg
Denaturant	dermal	LD50 - Rabbit - >2,000 mg/kg
	inhalation	LC50 - Rat - >5.2 mg/L
	oral	LD50 - Rat - >5,000 mg/kg
Ethanol	inhalation	LC50 - Rat - 124.7 mg/L (4 Hr)
	oral	LD50 - Rat - 10,470 mg/kg
Solvent naphtha (petroleum), light arom.	oral	LD50 - Rat - 8,400 mg/kg

Skin corrosion/irritation

Assessment: Causes severe skin burns and eye damage

Product data:

No data available.

Substance data:

Name	Result
Acetic Acid	Causes severe skin burns and eye damage.
Xylene	Causes skin irritation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 9 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

Name	Result
Nonyl phenol	Corrosive to the skin.

Serious eye damage/irritation

Assessment: Causes serious eye damage

Product data:

No data available.

Substance data:

Name	Result
Ethanol	Causes serious eye irritation.
Nonyl phenol	Corrosive to the eyes.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Suspected of causing cancer

Product data: No data available.

Substance data:

Name	Species	Result
Solvent naphtha (petroleum), light arom.	Not applicable.	Component may cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Ethanol	Group 1 - Carcinogenic to humans
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Solvent naphtha (petroleum), light arom.	May cause genetic defects.

Reproductive toxicity

Assessment: Suspected of damaging fertility or the unborn child

Product data:

No data available.

Substance data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 10 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

Name	Result
Ethanol	Reproductive toxicity - Human female - Oral (Effects on Newborn: Apgar score (human only) , other neonaal measures or effects and drug dependence.)
Nonyl phenol	Suspected human reproductive toxicant.

Specific target organ toxicity (single exposure)

Assessment: Causes damage to organs

Product data:

No data available.

Substance data:

Name	Result
Methanol	Causes damage to the optic nerve and central nervous system.
Ethyl Benzene	Specific Target Organ Toxicity, Repeated Exposure - May cause damage to hearing organs through prolonged or repeated exposure.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Ethyl Benzene	May be fatal if swallowed and enters airway.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Ethanol	LC50 - Pimephales promelas (fathead minnow) - 14, 200 mg/l - 96 h
	LC50 - Ceriodaphnia dubia (water flea) - 5, 012 mg/l - 48 h
	NOEC - Daphnia magna (water flea) - 9.6 mg/l - 9 d
	EC50 - Chlorella vulgaris (fresh water algae) - 275 mg/l - 72 h (OECD Test Guideline 201)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 11 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

Name	Result
Methanol	LC50 - Fish - 15,000 - 29400 mg/l - 96 h
	LC50 - Crustaceans - 2500 - 481000 mg/l - 48 h
Nonyl phenol	flow-through test LC50 - Lepomis macrochirus - 0.209 mg/l - 96 h
	semi-static test EC50 - Daphnia magna (Water flea) - 0.0844 mg/l - 48 h
	static test EC50 - Selenastrum capricornutum (green algae) - 0.33 mg/l - 72 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Ethanol	Result: 95 % - Readily biodegradable

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Ethanol	Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.


SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	UN 1987
UN proper shipping name	Alcohols, n.o.s. Ethanol, Gasoline
UN transport hazard class(es)	3 
Packing group	II
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	UN 1987
-----------	---------

Safety Data Sheet


According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018


Page 12 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

UN proper shipping name	Alcohols, n.o.s. Ethanol, Gasoline	
UN transport hazard class(es)	3	
Packing group	II	
Environmental hazards	None	
Special precautions for user	None	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN 1987	
UN proper shipping name	Alcohols, n.o.s. Ethanol, Gasoline	
UN transport hazard class(es)	3	
Packing group	II	
Environmental hazards	None	
Special precautions for user	None	

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

64-17-5	Ethanol	Listed
67-56-1	Methanol	Listed
64-19-7	Acetic Acid	Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
84852-15-3	Nonyl phenol	Listed

Significant New Use Rule (TSCA Section 5):

84852-15-3	Nonyl phenol	Listed
------------	--------------	--------

Export notification under TSCA Section 12(b):

84852-15-3	Nonyl phenol	Listed
------------	--------------	--------

SARA Section 302 extremely hazardous substances: Not determined.

SARA Section 313 toxic chemicals:

64-17-5	Ethanol	Not Listed
67-56-1	Methanol	Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
84852-15-3	Nonyl phenol	Listed

CERCLA:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 13 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

67-56-1	Methanol	Listed	5000
1330-20-7	Xylene	Listed	100
100-41-4	Ethyl Benzene	Listed	1000

RCRA:

67-56-1	Methanol	Listed	U154
1330-20-7	Xylene	Listed	U239

Section 112(r) of the Clean Air Act (CAA):

67-56-1	Methanol	Listed
---------	----------	--------

Massachusetts Right to Know:

64-17-5	Ethanol	Listed
67-56-1	Methanol	Listed
64-19-7	Acetic Acid	Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
84852-15-3	Nonyl phenol	Listed

New Jersey Right to Know:

64-17-5	Ethanol	Listed
67-56-1	Methanol	Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
84852-15-3	Nonyl phenol	Not Listed

New York Right to Know:

64-17-5	Ethanol	Listed
67-56-1	Methanol	Listed
64-19-7	Acetic Acid	Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
84852-15-3	Nonyl phenol	Not Listed

Pennsylvania Right to Know:

64-17-5	Ethanol	Listed
67-56-1	Methanol	Listed
64-19-7	Acetic Acid	Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
84852-15-3	Nonyl phenol	Listed

California Proposition 65:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.29.2018

Page 14 of 14

Revision date: 05.14.2018

WarFighter Fuel Treatments Corrosion Spray

WARNING: This product contains a chemical known to the State of California to cause cancer.

100-41-4

Ethyl Benzene

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

67-56-1

Methanol

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-3-0

HMIS: 3-3-0

Initial preparation date: 03.29.2018

Revision date: 05.14.2018

End of Safety Data Sheet